



# BLANKOL-5006

**Art.-No. 4 06110**

## Special release agent for the concrete industry

BLANKOL-5006 is an environmentally friendly, high-quality release agent, which does not support build-ups and reduces the formation of superficial pores due to selected active components.

### Areas of application:

BLANKOL-5006 has been particularly designed for the precast element production.

### Technical Data:

Colour: clear, yellowish  
Form: liquid  
Density: 0.8 g/cm<sup>3</sup>  
Storage: cool and dry, 24 month, when stored in the original unopened container. Use opened containers promptly.  
Packaging: 1.000 l IBCs  
                  210 l drums  
                  25 l cans

### Instructions for Use:

BLANKOL-5006 is to be sprayed regularly and as thin as possible onto the clean and dry mould.

### Important advice:

- Suitability tests should be carried out prior to usage.
- Avoid puddles!
- Excessive coating can lead to incrustations and build-ups.
- Only use spray nozzles with a maximum diameter of 1 mm.
- Do not drain off the treated surfaces, but wipe up surplus release agent with a mineral oil resistant squeegee.
- BLANKOL-5006 is not water soluble.
- Welding, flying sparks, open fire etc. must be absolutely avoided next to freshly treated moulds.

Please adhere to the EU Safety Data Sheet!

**GISCODE: BTM 10**