

AUTOMATIC PUMICE CONCRETE-BRICK-CONCRETE BLOCK COMPRESSION TESTING MACHINE

STANDARDS: EN 772-1

The LIYA Automatic range of 1200 kN and 3000 kN capacity compression testing machine has been designed for reliable and consistent testing of a Pumice Concrete, Brick and Concrete Blocks of specimens.

The dimensions of the upper and lower plates allow the testing of sample on 510x310x50 mm compression plates, concrete blocks and building materials.

Tests can be performed by either Digital Readout Unit or on a computer with using free Software.

The Automatic Pumice Concrete-Brick-Concrete Block Compression Testing Machines allow inexperienced operators to perform the tests. Once the machine has been switched on and the specimen is positioned and centered by the help of centering apparatus. The only required operations are;

- Setting test parameters, including pace rate (only required when the specimen type is changed).
- Pressing the START button on the control unit
- The machine automatically starts the rapid approach, when the specimen touches the upper platen the rapid approach is ended and starts loading at the pace rate that selected by user and stops once the specimen fails.



79

The Automatic Pumice Concrete-Brick-Concrete Block Compression Testing Machine consist of;

Load Frame,

Automatic Hydraulic Power Pack,

Digital data acquisition & control system,

Distance Pieces, Ø 205x25 mm and Ø 205x50 mm

Upper Platen (with ball seating assembly) 510x310x50 mm,

Lower Platen 510x310x50 mm,

Loading Cylinder Assembly & Limit Switch for safety,

Pumice Concrete-Brick-Concrete Block Compression Load Frame

The Load Frame is made of welded steel walls the piston is placed in the center of frame.

The load frame provides the stability needed for accurate and repeatable test results over the years of operation.

Upper Platens/Lower Platens

Upper Platen (with ball seating assembly) 510x310x50 mm and Lower Platen 510x310x50 mm.

- Manufactured from high quality steel, which is then hardened, smoothed and finished.
- The roughness value for the surface texture of the auxiliary platens is $\leq 3.2 \mu\text{m}$.



Distance Pieces

Distance pieces are used to reduce the amount of vertical clearance between the upper platen and the lower platen. Supplied with Ø205 mm distance pieces.



Loading Cylinder Assembly & Limit Switch

All frames have a single acting up stroking ram. The diameter of piston changes with regard to the capacity.

The maximum ram stroke is 50 mm, a limit switch is fitted to prevent over travel of the ram which cuts the power to the pump for safety.

At the end of the test process to start a new test the piston returns to default position.

The pressure transducer is used for load measurements.

There is a low friction coaxial PTFE seal between the cylinder and the piston fitted to the cylinder.

HYDRAULIC POWER PACK AND DIGITAL DATA ACQUISITION & CONTROL SYSTEM

Hydraulic Power Pack

80

Automatic Hydraulic Power Pack, dual stage, controlled by digital readout unit is designed to supply the required oil to the load frames for loading.

Controller unit has a simple and compact configuration. The Hydraulic Power Pack is equipped with 4 wheels for easy carriage and flexible installation

Very silent power pack can load the specimen between 1 kN/sec. to 20 kN/sec, with an accuracy of $\pm 5\%$. A Rapid approach pump is supplied as standard. Safety valve (maximum pressure valve) is used to avoid machine overloading.

Maximum working pressure of the system is 410 bar.

Dual Stage Pump

The dual stage pump is formed by two groups;

- 1.Low pressure gear pump
- 2.High pressure radial piston pump

On the dual stage pump, a high delivery, low pressure gear pump is used for rapid approach, while a low delivery, high pressure radial piston pump is used for test execution. The rapid approach facility shortens the time interval from piston start until the upper platen touches to the specimen. This excellent feature helps to save a lot of time when a large number of specimens are going to be tested.



Motor

The motor which drives the dual pumps in an AC motor and it is controlled by motor inverter. The variation in the oil flow is executed with the variation of the rotation speed of the motor.

Distribution Block

A distribution block is used to control the oil flow direction supplied by the dual stage pump, the following parts are fitted to the distribution block; Solenoid valve, Safety valve (max. pressure valve), Transducer, Low pressure gear pump and High pressure radial piston pump.

**High Precision Pressure Transducer**

The LIYA range of Semi-Automatic and Automatic Machines can be upgraded with option High Precision Pressure Transducer special calibration Class 1 starting from 1% of the full range.

This unique performance enables the machines to be used for a considerable number of applications including:

- Early age(2 or 3 days) compression strength tests
- Flexural and splitting tests by using proper accessories
- Mortar (Cement) compression tests by using proper accessories
- Core Testing

**Oil Tank**

The tank includes enough oil to fill the mechanism which pushes the ram during the test. The level and oil temperature can be seen on the indicator fitted to the tank. It has 25 L capacity. Hydraulic motor oil, number 46, must be used.

**Digital Data Acquisition & Control System**

The unit is designed to control the machine and processing of data from load-cells and pressure transducers which are fitted to the machine.

All the operations of the unit is controlled from the front panel consisting of a LCD display and function keys.

The unit has easy to use menu options.

Digital graphic display unit loading rate of the time of Testing and load values can be monitored.

Digital graphic display is able to draw real-time "Load vs. Time".

Software

Sample, company, laboratory and test values can be entered in the programme.

Load-time graphic, test reports and sample reports can be taken.

Software provides test data, results, and the load-time graphs can be seen at LCD screen.

The Automatic Compression machine can be controlled (Start, Stop commands) by a computer with the software free of charge. This software provides data acquisition and management for compression, tensile and splitting tensile test throughout the test execution. The advanced functions for data base management provide an easy navigation of all saved data. The test results certificate includes all descriptive information. Therefore, test parameters can be set and details about the test carried out such as client details, test type, specimen type, user info and other information required can be entered and printed out as well as test report and graph.

Software can be performed in Turkish and English.

Test results, graphics and properties of 24 different specimens can be saved in one folder. Old test folders can be reviewed.


User can highlight all 12 different specimen curves in different colors on the graphics.

Frequently used information like name and location of the laboratory, type and dimensions of mostly used specimens are held in memory and can be written automatically by right clicking on information boxes and selecting frequently used text in menu.

User can access any data of previously completed tests and use in his/ her new report since most of the tests have same structure and properties.

Main Features

- Pace rate control from 1 kN/sec to 20 kN/sec depending on piston size.
- Can control 2 frames (optional)
- Can make test with load control.
- Real time display of test graph.
- Analog channels for different frame load cells
- RS-232 serial port connecting for computer interface
- LCD display
- 2 different unit system selection; kN and kgf
- Multi-language support (English and Turkish)
- 2 different unit system selection; SI and Metric
- Real-time clock and date
- Free of charge PC software for the test control and printout the test report.



Technical Specifications

Product Name	Automatic Pumice Concrete-Brick-Concrete Block Compression Testing Machine
Product Code	LT-C1200
Capacity (kN)	120
Roughness (μm)	≤ 3.2
Lower Platen (cm)	51x30x5
Upper Platen (cm)	51x30x5
Max. Vertical clearance (cm)	25
Piston diameter (cm)	20
Piston Stroke(cm)	5
Horizontal clearance (cm)	31
Thickness of platens (cm)	5
Hardness of Platens (HRC)	55-60
Oil Capacity (lt)	25
Max. Working Pressure (bar)	410
Power (W)	750

Safety Features

- Maximum pressure valves to avoid machine overloading
- Piston travel limit switch
- Emergency stop button
- Software controlled maximum load value

Technical Specifications

Product Code	Product Name	Dimensions (cm)	Weight (kg)	Power Supply
LT-C1200	1200 kN Automatic Pumice Concrete-Brick-Concrete Block Compression Testing Machine	75x60x100	600	220 V, 50-60 Hz, 1 ph
LT-C1200/1	1200 kN Load Frame	37x60x100	500	---
LT-C0225	Hydraulic Power Pack and Digital Data Acquisition & Control System	38x36x92	100	220 V, 50-60 Hz, 1 ph
LT-C0226	Hydraulic Power Pack	38x36x92	98	220 V, 50-60 Hz, 1 ph
LT-C0227	Digital Data Acquisition & Control System	---	---	220 V, 50-60 Hz, 1 ph
LT-C0228	High Precision Pressure Transducer	---	---	---
LT-C0229	Software	---	---	---
LT-C0235	Distance Pieces	$\varnothing 20,5 \times 2,5$	---	---
LT-C0236	Distance Pieces	$\varnothing 20,5 \times 5$	---	---
LT-G0800	Computer & Printer	---	---	220 V, 50-60 Hz, 1 ph