

## CYLINDER MOULDS

**STANDARDS:** EN 12390-1, ASTM C39, C192

Hard plastic or steel cylinder moulds are manufactured in accordance to dimensions and tolerances stated in the related standards. Two part and clamp attached base plate plastic and steel moulds are designed to be durable, resistant and easy to clean.

### Technical Specifications

Product Code	Product Name	Int. Dimensions (cm)	Ext. Dimensions (cm)	Weight (kg)
LT-C0010	Plastic Cylinder Mould	10x20	16x16x21	1
LT-C0011	Steel Cylinder Mould	10x20	16x16x21	6
LT-C0012	Plastic Body with Steel Plate Cylinder Mould	10x20	16x16x21	1,5
LT-C0013	Plastic Cylinder Mould	15x30	25x25x31	1,5
LT-C0014	Steel Cylinder Mould	15x30	25x25x31	9
LT-C0015	Plastic Body with Steel Plate Cylinder Mould	15x30	20x20x31	2
LT-C0016	Steel Cylinder Mould	25x50	35x35x51	12,5



## BEAM MOULDS

**STANDARDS:** EN 12390-1, ASTM C39, C192

Steel beam moulds are manufactured in accordance to dimensions and tolerances stated in the related standards. Two part and clamp attached base plate steel moulds are designed to be durable, resistant and easy to clean.

### Technical Specifications

Product Code	Product Name	Int. Dimensions (cm)	Ext. Dimensions (cm)	Weight (kg)
LT-C0018	Steel Beam Mould	10x10x40	17x51x15	18,5
LT-C0019	Steel Beam Mould	10x10x50	17x60x16	20,5
LT-C0020	Steel Beam Mould	15x15x60	22x70x22	38,5
LT-C0021	Steel Beam Mould	15x15x75	22x85x22	40



## POKER VIBRATOR

**STANDARDS:** EN 12390-2, ASTM C31, C192

Poker Vibrator is ideal for the international compaction of concrete specimens and a good alternative to traditional tamping bar especially when there are large numbers of specimens to be compacted.

Vibrating Head diameter and Hose height can be also selected upon user's request.

### Technical Specifications

Product Code	Product Name	Vibrating Head dia. (cm)	Hose Height (m)	Frequency (rpm)	Dimensions (cm)	Weight (kg)	Power Supply
LT-C0045	Poker Vibrator	Ø3,2	3	12000	40x16x24	6,5	220 V, 50-60 Hz, 1 ph
LT-C0046	Poker Vibrator	Ø3,8	4	18000	40x16x24	6,5	220 V, 50-60 Hz, 1 ph
LT-C0047	Poker Vibrator	Ø4,5	4	18000	40x16x24	6,5	220 V, 50-60 Hz, 1 ph
LT-C0048	Poker Vibrator	Ø5	5	18000	40x16x24	6,5	220 V, 50-60 Hz, 1 ph

