



# Declaration of Performance

according Annex III of the Regulation (EU) No. 305/2011

for the product

## AQUAFIN-2K

204250

1. **Unique identification code of the product type:** EN 14891 CM
2. **Identification :** batch no.: see packaging of the product
3. **Intended use:** Liquid applied cement based waterproofing product for use under ceramic tiles in exterior areas
4. **Manufacturer :** Schomburg GmbH & Co. KG  
Aquafinstrasse 2-8  
32760 Detmold
5. **Authorized representative:** not relevant
6. **System or systems of assessment and verification of constancy of performance of the construction product as:** System3
7. **Notified test laboratory:**  

The notified testing laboratory  
KIWA Bautest Dresden,  
identification number 2007  
performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No **P-2002-4-1023/02B.**

The notified testing laboratory  
KIWA Polymer Institut,  
identification number 1119  
performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No **P- 8599-3.**
8. **Declared performance :**

Essential characteristic	Performance	Harmonised technical specification
Initial adhesive tensile strength	$\geq 0,5 \text{ N/mm}^2$	EN 14891:2012
Tensile adhesion strength after water immersion	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	
Adhesive tensile strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$	



Essential characteristic	Performance	Harmonised technical specification
Water impermeability	No water penetration	
Crack bridging	$\geq 0,75$ mm	
Dangerous ingredients	NPD	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Signed for and on behalf of the manufacturer by:**

Wilhelm-Kreyling Dreyer, technician  
(name and function)

Detmold, 11.02.2014

**This declaration of performance was created electronically. It is valid without manual signature.**

The current material safety data sheet and technical data sheet is downloadable under

[http://www.schomburg.de/en/Materials\\_Safety\\_Data\\_Sheet\\_MSDS-datenblaetter.html](http://www.schomburg.de/en/Materials_Safety_Data_Sheet_MSDS-datenblaetter.html)

or

[http://www.schomburg.de/en/Technical\\_Data\\_Sheet-datenblaetter.html](http://www.schomburg.de/en/Technical_Data_Sheet-datenblaetter.html)