

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 02.05.2016

Version number 13

Revision: 02.05.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Asodur-K 900 (A-Komp.)**
- **Article number:** 205070
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Epoxy coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SCHOMBURG GmbH & Co. KG
Aquafinstr. 2-8
D-32760 Detmold
Germany

Tel: ++49 (0)5231/953-00
Fax: ++49 (0)5231/953-123
email: info@schomburg.de
web: www.schomburg.de
- **Informing department:**
Product Safety Department

Tel: ++49 (0)5231/953-193
Fax: ++49 (0)5231/953-106
email: guido.herfort@schomburg.de

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** GHS07, GHS09
- **Signal word** Warning
- **Hazard-determining components of labelling:**
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)
bisphenol-F-epoxy resin
1,6-bis(2,3-ethoxypropoxy)hexane
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 1)

Precautionary statements

- P273 Avoid release to the environment.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P363 Wash contaminated clothing before reuse.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains epoxy constituents. May produce an allergic reaction.





2.3 Other hazards**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures****Description:**

Solvent- free preparation based on Bisphenol-A-Epichlorhydrin resin molecular weight ≤ 700 .

Dangerous components:

CAS: 25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number	50-100%
NLP: 500-033-5	average molecular weight = 700)	
		
CAS: 38640-62-9	Diisopropylnaphtalene	10-25%
		
CAS: 9003-36-5	bisphenol-F-epoxy resin	2,5-10%
NLP: 500-006-8		
CAS: 16096-31-4	1,6-bis(2,3-ethoxypropoxy)hexane	2,5-10%
		

- **Additional information** For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Personal protection for the First Aider.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

It is possible to choke in case of vomiting in unconsciousness.

Bring unconscious persons into a stable position on side.

Keep the respiratory tract free (remove dentures and vomiting).

Check the pulse. In case of heart failure you have to make a cardiac massage. In case of stoppage of breathing: artificial respiration.

Take up a doctor immediately!

- **After inhalation** Supply fresh air or oxygen; call for doctor.

After skin contact

Don't use solvents to clean the skin.

Instantly wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 2)

- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.
- **After swallowing**
Do not induce vomiting; instantly call for medical help.
Show the pack or the label to the doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Formation of poisonous gases during heating or in fires.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained breathing apparatus.
- **Additional information**
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Follow the emergency-plan.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Avoid eye- and skin contact.
Do not breath in vapour.
Keep away from ignition sources
Bring persons out of danger.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or water bodies.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding, inflammable material (sand, diatomite, acid binders, universal binder).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Keep containers tightly sealed.
Work with fresh air supply, keep doors and windows open.
Keep away from heat and direct sunlight.
Keep away from children.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Do not leave open containers.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Please follow the rules of the VCI-Storage-Concept for chemicals.

(Contd. on page 4)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 3)

- **Further information about storage conditions:**
Protect from frost.
Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:**
It must be possible to wash the skin in the working area.
Eye-wash bottle must be available.
- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the compilation were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**
Clean skin only with cleaning agent especially for epoxy resin.
Don't use solvent for skin cleaning!
Clean clothes which are contaminate with epoxi resin before unusing again.
The usual precautionary measures should be adhered to in handling the chemicals.
Instantly remove any soiled and impregnated garments.
Avoid contact with the eyes and skin.
Be sure to clean skin thoroughly after work and before breaks.
- **Breathing equipment:**
In not so good ventilated space the filter combination A2B2E2K1HgP3RD is to be used.
- **Protection of hands:** Hand Protection: Nitril-rubber-latex-gloves.
- **Material of gloves**
Butyl rubber II R: Thickness $\geq 0,5\text{mm}$; Break through time $\geq 480\text{ min}$
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Safety glasses
- **Body protection:**
Protective work clothing.
Contaminated protection clothes must be cleaned carfully before reuse.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Colour:	Colourless
Smell:	Type specific
- **Change in condition**

Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined
- **Flash point:** Not applicable
- **Self-inflammability:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive.

(Contd. on page 5)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 4)

- | | |
|--|--|
| · Density at 20 °C | 1,13 g/cm ³ |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix |
| · Viscosity: | |
| dynamic at 20 °C: | 1500 mPas |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts violently with oxidizing agents
Reacts with strong acids and oxidizing agents
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Can react with acid and oxidizing agents.
- **10.6 Hazardous decomposition products:**
In case of heating dangerous decomposition products can be arise.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values that are relevant for classification:**
- | | | | |
|--|----------|---------------------|--|
| 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) | | | |
| Oral | LD50 | >5000 mg/kg (rats) | |
| Dermal | LD50 | >2000 mg/kg (rats) | |
| 38640-62-9 Diisopropylnaphtalene | | | |
| Oral | LD50 | >3900 mg/kg (rats) | |
| Dermal | LD50 | >4500 mg/kg (rats) | |
| 9003-36-5 bisphenol-F-epoxy resin | | | |
| Oral | LD50 | >10000 mg/kg (rats) | |
| Dermal | LD50 | >2000 mg/kg (rats) | |
| 16096-31-4 1,6-bis(2,3-ethoxypropoxy)hexane | | | |
| Oral | LD50 | 1400 mg/kg (rabbit) | |
| | | 2900 mg/kg (rats) | |
| Inhalative | LC50/4 h | >100 mg/l (Maus) | |
- **Primary irritant effect:**
 - **Skin corrosion/irritation**
Causes skin irritation.
 - **Serious eye damage/irritation**
Causes serious eye irritation.
 - **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
 - **Additional toxicological information:** Sensitizing
 - **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
 - **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 5)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· **Aquatic toxicity:**

25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)

LC50 (96h) 2 mg/l (rainbow trout)

EC50 (48h) 1.7 mg/l (Daphnia sp.)

EC50 (48h) 1.7 mg/l (Daphnia magna)

NOEC 0.3 mg/l (Daphnia magna)

9003-36-5 bisphenol-F-epoxy resin

LC50/96h 2.54 mg/l (Leuciscus idus)

EC50 2.55 mg/l (Daphnia magna)

ERC50 1.8 mg/l (algae toxicity)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

17 00 00 CONSTRUCTION AND DEMOLITION WASTES (INCLUDING EXCAVATED SOIL FROM CONTAMINATED SITES)

17 02 00 wood, glass and plastic

17 02 03 plastic

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.


GB

(Contd. on page 7)

Trade name: **Asodur-K 900 (A-Komp.)**

(Contd. of page 6)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA 	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalin-Isomere)
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	
<ul style="list-style-type: none"> · Class · Label 	9 Miscellaneous dangerous substances and articles. 9
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA): 	Yes Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Kemler Number: · EMS Number: 	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · ADR · Limited quantities (LQ) · Transport category · Tunnel restriction code 	5L 3 E
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol A-(epichlorhydrin); epoxy resin(number average molecular weight<700), Diisopropylnaphthalene), 9, III

GB

(Contd. on page 8)

Trade name: Asodur-K 900 (A-Komp.)

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Water hazard class:**
Water hazard class 2 (Self-assessment): hazardous for water.
The classification based on german instructions.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H413 May cause long lasting harmful effects to aquatic life.
- **Department issuing data specification sheet:** Environment protection department.
- **Contact:** Mr. Guido Herfort
- **Abbreviations and acronyms:**
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3
Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4
- *** Data compared to the previous version altered.**